Resale Inspection Check List. Not all items are listed however these are the most commonly found during an inspection.		
	All Permits pulled shall be been paid, completed and passed zoning and building inspection. Provide proof of permits and inspections.	
	If a property owner is deceased. Provide a copy of the Short Certificate or Power of Attorney authorizing individual(s) to sell the property.	
	House shall be clearly identified on the Building and on one side of the mail box. Numbers should be Arabic numbers or alphabet letters, Minimum of 4 inches high and a minimum stroke width of 0.5 inch - 304.3	
	All Exterior surfaces shall be maintained in good condition - 304 Exterior Structures (including 304 subsections - Foundation walls, roofs, drainage, etc.) – 302 Exterior Areas, 302.1 , 302.1 , 302.3 , 302.7	
	Vegetation at the exterior walls shall be trimmed back from the exterior siding to prevent moisture damage. -302.4	
	Interior surfaces shall be clean and maintained in good condition including but not limited to structural members, interior surfaces, stairs, walking surfaces, handrails, guards doors – 305	
	Interior doors and windows shall open and close smoothly without interruption and all hardware functions properly. 305.6	
	Locks, All egress doors shall have a throw-bolt type of lock. Not a lock that uses a key or requires special knowledge to exit the dwelling 702.3	
	Smoke Detectors in each room used for sleeping purposes, one outside the sleeping area(s), one on every floor including basement (not required for crawl spaces and uninhabitable attics) 704.2	
	Carbon monoxide detector – Homes built under 2009 Building Codes. For homes built prior to 2009 Building Codes it is strongly recommended to install a least one carbon monoxide detector outside the sleeping rooms if you are burning fossil fuels to heat your home or have an attached garage.	
	Ventilation – Habitable spaces shall have at least one openable window and shall conform to the minimum glazed area required in Section 402.1 403.1.	
	Dryer exhaust – Replace vinyl flexible dryer exhaust hose with UL listed (metallic) flexible dryer exhaust hose 403.5.	

Thermostat Pressure Release "TPR" pipe on a hot water heater or boiler shall have a 3/4" diameter pipe extending within 6-inches of the floor 505.4.1
Bathroom floor surface shall be maintained to be a smooth, hard, nonabsorbent surface. – 503.4.
All plumbing fixtures, sink, tub, lavatories, laundry tubs and showers shall be property connected to either a public water system or to an approved private water system. And shall be supplied with hot or tempered and cold running water. 505.1
Maintain clearances/areas; remove all combustible materials around all fuel burning equipment. – 603.3
GFCI protected receptacles located within 6-feet from the edge of a sink, tub, or laundry tub. 604.3
Outside receptacles shall be GFCI protected and have a protective cover or bubble cover that is rated for outdoor use. 604.3
Electrical Box and Connections Install a cover plates at each ceiling junction box with exposed wiring 604.3
Electric panel box - Install knockout bushings in openings at the main service panel 604.3
Fire rated door separating the garage from living space. Door shall be fire rated, solid wood doors not less than 1-3/8" thick, solid or honeycomb core steel doors not less than 1-3/8 inches thick, or 20-minute fire-rated doors. 703.2
Swimming pool barrier - where the house is used as a barrier, all doors accessing the pool area shall be equipment with an audible alarm. Such alarm shall sound continuously for a minimum of 30 seconds immediately after the door is opened and be capable of being heard throughout the house during normal house-hold activities. The alarm shall automatically reset under all conditions. – 303.2, IRC Appendix G.
Swimming pools - access gates shall open away from the pool area and shall be equipped with a self-closing and self-latching device. 303.2

Free E-Codes - International 2009 Building Code and 2009 Property Maintenance Code is available online. http://publicecodes.citation.com/icod/index.htm